

MODEL



E.-ATV 1190 RC8-R

Engine Type 1195cm Liquid Cooled KTM-Engine, 4-Stroke, 2 Cylinder, 4 valves
Engine Power 129 KW / 175 HP
Bore x Stroke 105 x 69 mm
Torque 127 Nm at 8000 Rpm
Compression Ratio 13,5 : 1
Fuel Delivery Electronic Injection Keihin
Starter / Battery E-Starter 12V / 11,2 Ah
Transmission 6 Gears, Wet Multi Disc Clutch, Operated Hydraulically
Lubrication Pressure Lubrication
Drive Train Chain drive / solid axle

Frame 25CrMo4
Handlebar Aluminium 6060
Suspension Front Twin A-Arms With Fully Adjustable Promax Suspension Shocks
Susp. Travel Front 200 mm
Suspension Rear Eccenter - Swingarm With Link-System & Central, Adjustable WP Suspension Shock
Susp. Travel Rear 120 mm
Brake Front 2 Brembo 2-Piston Floating Caliper
Brake Rear 1 Brembo 2-Piston Floating Caliper
Tires Front 165 x 70 - 10
Tires Rear 225 x 40 - 10
Rims Douglas Wheel LiteCast Street-Rok
Track Width 1295 mm
Wheelbase 1525 mm
Dry Weight 230 kg
Fuel Capacity 16,5 Litre

Road Legal Yes / EU homologated

Colour freely selectable

Price incl. VAT 34.900,00 €

ENGINE

CHASSIS

OTHER



Superiority across the board



Please wear a helmet, eye protection and protective clothing. Always ride in responsible manner, respecting the environment as well as all state and local laws.

E.-ATV Racing GmbH • Vluynenstr. 44 • 47506 Neukirchen-Vluyn

phone: +49 (0)2845 377837 • fax: +49 (0)2845 377835

E-Mail: info@eatv.de

www.eatv.de



Specifications subject to change without notice. All ATVs come with a 24-month Limited Factory Warranty on KTM Parts and a 36-month Limited Factory Warranty on E.-ATV Parts. See your dealer for details.. © Copyright 2009 - E.-ATV Racing

**E.-ATV 450 SX-F**

Engine Type	449 ccm Liquid Cooled KTM-Engine, 4-Stroke, 1 Cylinder, 4 Valve, DOHC
Engine Power	39 KW / 53 HP
Bore x Stroke	97 x 60,8 mm
Torque	Not Reported
Compression Ratio	12,5 : 1
Fuel Delivery	Keihin Carburetor FCR-MX 41
Starter / Batterie	E-Starter 12V / 4 Ah
Transmission	4 Gears, Wet Multi Disc Clutch, Operated Hydraulically
Lubrication	Pressure Lubrication
Drive Train	2WD, Sealed O-Ring Chain, Solid Axle
Frame	Chromoly
Handlebar	Magura Tapered Aluminium, Ø 28 mm
Suspension Front	Twin A-Arms With Fully Adjustable WP Suspension Shocks
Susp. Travel Front	250 mm
Suspension Rear	Eccenter - Swingarm With Central Fully Adjustable WP Suspension Shock
Susp. Travel Rear	275 mm
Brake Front	2 Brembo 2-Piston Floating Caliper
Brake Rear	1 Brembo 2-Piston Floating Caliper
Tires Front	21 x 7,00 - 10
Tires Rear	20 x 11,00 - 9
Rims	Douglas Wheel AlumiLite Sport Red
Track Width	1295 mm
Wheelbase	1305 mm
Dry Weight	175 kg
Fuel Capacity	8 Litre
Road Legal	None
Colour	freely selectable
Price incl. VAT	15.900,00 €

**E.-ATV 690 E**

Engine Type	654 ccm Liquid Cooled KTM-Engine, 4-Stroke, 1 Cylinder, 4 Valve, OHC
Engine Power	46,3 KW / 63 HP
Bore x Stroke	102 x 80 mm
Torque	64 Nm at 6000 Rpm
Compression Ratio	11,8 : 1
Fuel Delivery	Electronic Fuel Injection Keihin EMS With ETP (Electronic Power Throttle)
Starter / Batterie	E-Starter 12V / 8,6 Ah
Transmission	6 Gears, APTC Slipper Clutch, Operated Hydraulically
Lubrication	Pressure Lubrication With 2 Eaton Pumps
Drive Train	2WD, Sealed O-Ring Chain, Solid Axle
Frame	Chromoly
Handlebar	Magura Tapered Aluminium, Ø 28 mm
Suspension Front	Twin A-Arms With Fully Adjustable WP Suspension Longtravel Shocks
Susp. Travel Front	250 mm
Suspension Rear	Eccenter - Swingarm With Central Fully Adjustable WP Suspension Shock
Susp. Travel Rear	275 mm
Brake Front	2 Brembo 2-Piston Floating Caliper
Brake Rear	1 Brembo 2-Piston Floating Caliper
Tires Front	21 x 6,00 - 10
Tires Rear	20 x 10,00 - 9
Rims	Douglas Wheel AlumiLite Sport Red
Track Width	1295 mm
Wheelbase	1305 mm
Dry Weight	195 kg
Fuel Capacity	12 Litre
Road Legal	Yes / EU homologated
Colour	freely selectable
Price incl. VAT	17.990,00 €

**E.-ATV 990 ADV-R**

Engine Type	999 ccm Liquid Cooled KTM-Engine, 4-Stroke, 2 Cylinder, 4 Valve, DOHC
Engine Power	78 KW / 106 HP
Bore x Stroke	101 x 62,4 mm
Torque	100 Nm at 6750 Rpm
Compression Ratio	11,5 : 1
Fuel Delivery	Electronic Fuel Injection Keihin
Starter / Batterie	E-Starter 12V / 11,2 Ah
Transmission	6 Gears, Wet Multi Disc Clutch, Operated Hydraulically
Lubrication	Pressure Lubrication
Drive Train	2WD, Sealed O-Ring Chain, Solid Axle
Frame	Chromoly
Handlebar	Magura Tapered Aluminium, Ø 28 mm
Suspension Front	Twin A-Arms With Fully Adjustable WP Suspension Shocks
Susp. Travel Front	200 mm
Suspension Rear	Eccenter - Swingarm With Central Fully Adjustable WP Suspension Shock
Susp. Travel Rear	150 mm
Brake Front	2 Brembo 2-Piston Floating Caliper
Brake Rear	1 Brembo 2-Piston Floating Caliper
Tires Front	165 x 70 - 10
Tires Rear	225 x 40 - 10
Rims	Douglas Wheel Litecast Street-Rok
Track Width	1295 mm
Wheelbase	1495 mm
Dry Weight	245 kg
Fuel Capacity	22 Litre
Road Legal	Yes / EU homologated
Colour	freely selectable
Price incl. VAT	23.900,00 €

**E.-ATV 990 SM-R**

Engine Type	999 ccm Liquid Cooled KTM-Engine, 4-Stroke, 2 Cylinder, 4 Valve, DOHC
Engine Power	85 KW / 115 HP
Bore x Stroke	101 x 62,4 mm
Torque	97 Nm at 7000 Rpm
Compression Ratio	11,5 : 1
Fuel Delivery	Electronic Fuel Injection Keihin
Starter / Batterie	E-Starter 12V / 11,2 Ah
Transmission	6 Gears, Wet Multi Disc Clutch, Operated Hydraulically
Lubrication	Pressure Lubrication
Drive Train	2WD, Sealed O-Ring Chain, Solid Axle
Frame	Chromoly
Handlebar	Magura Tapered Aluminium, Ø 28 mm
Suspension Front	Twin A-Arms With Fully Adjustable WP Suspension Shocks
Susp. Travel Front	200 mm
Suspension Rear	Eccenter - Swingarm With Central Fully Adjustable WP Suspension Shock
Susp. Travel Rear	120 mm
Brake Front	2 Brembo 2-Piston Floating Caliper
Brake Rear	1 Brembo 2-Piston Floating Caliper
Tires Front	165 x 70 - 10
Tires Rear	225 x 40 - 10
Rims	Douglas Wheel Litecast Street-Rok
Track Width	1295 mm
Wheelbase	1495 mm
Dry Weight	240 kg
Fuel Capacity	19 Litre
Road Legal	Yes / EU homologated
Colour	freely selectable
Price incl. VAT	23.900,00 €

**E.-ATV 990 SD-R**

Engine Type	999 ccm Liquid Cooled KTM-Engine, 4-Stroke, 2 Cylinder, 4 Valve, DOHC
Engine Power	97 KW / 132 HP
Bore x Stroke	101 x 62,4 mm
Torque	102 Nm at 8000 Rpm
Compression Ratio	11,5 : 1
Fuel Delivery	Electronic Fuel Injection Keihin
Starter / Batterie	E-Starter 12V / 11,2 Ah
Transmission	6 Gears, Wet Multi Disc Clutch, Operated Hydraulically
Lubrication	Pressure Lubrication
Drive Train	2WD, Sealed O-Ring Chain, Solid Axle
Frame	Chromoly
Handlebar	Magura Tapered Aluminium, Ø 28 mm
Suspension Front	Twin A-Arms With Fully Adjustable WP Suspension Shocks
Susp. Travel Front	200 mm
Suspension Rear	Eccenter - Swingarm With Central Fully Adjustable WP Suspension Shock
Susp. Travel Rear	120 mm
Brake Front	2 Brembo 2-Piston Floating Caliper
Brake Rear	1 Brembo 2-Piston Floating Caliper
Tires Front	165 x 70 - 10
Tires Rear	225 x 40 - 10
Rims	Douglas Wheel Litecast Street-Rok
Track Width	1295 mm
Wheelbase	1495 mm
Dry Weight	235 kg
Fuel Capacity	18,5 Litre
Road Legal	Yes / EU homologated
Colour	freely selectable
Price incl. VAT	24.900,00 €

